

LW 230 ES



The LW 230 ES is ideal for dive shops, diving clubs and diving schools, as well as medium-sized breathing air filling station. The three-stage compressor is sound insulated and operates at low speed. It is also suitable for continuous operation. It offers long service intervals, low maintenance costs and, through the oversized industrial components maximum reliability. It comes fully wired with star/delta start cycle.



LW 230/280 ES
with optional ECC control

LW 280 ES - Inner view

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld/Germany

Phone: +49 (0)62 56 - 8 58 80 -0
Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com
Internet: www.lw-compressors.com

LW 230 ES



Specifications

- » Electro motor (E-Motor / 400V / 3 Phase / 50 Hz)
- » Painted steel housing (RAL 6026)
- » Sound insulated housing
- » Automatic condensate drain
- » Automatic stop at final pressure
- » Hour counter
- » Operating panel with start/stop and condensate test button, as well emergency stop switch
- » 2 x Filling hose c/w filling valve
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Low pressure oil pump and filter
- » Oil- / Water separators in stainless steel
- » Safety valves after each stage
- » 3x concentric suction/pressure valves
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

Options

- » Auto start system
- » Up to 6 additional hoses available
- » 200 and 300 bar parallel filling pressures
- » Motor protection switch
- » Oil pressure gauge
- » Intermediate pressure gauges
- » Oil pressure monitoring c/w auto shut down
- » Cylinder head temperature monitoring with auto shut down
- » Oil temperature display with auto shut down
- » 0.8 ltr. Prefilter (Enlarged the lifetime of the filter by approx. 5 h)
- » 2.3 ltr. Filter housing (Filter capacity: 1200 m³ at +20°C)
- » Puracon filter monitoring (Auto shut down also available)
- » ECC control
- » Phase monitoring c/w shut down at wrong direction of rotation
- » Additional high pressure outlet
- » Power cable and plug
- » Special voltages / frequencies on request

Technical Data

LW 230 ES	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm ³ /h] / [cfm]:	230 / 13.8 / 8.1
Max. Pressure [bar]:	350
RPM [1/min]:	1080
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor / 400V / 3 Phase / 50 Hz
Drive power [kW] with 50 Hz / 60 Hz:	5.5 / 6.6
Cooling air req. [m ³ /h] with 50 Hz / 60 Hz:	1650 / 1980
Lubrication type:	Oil pump + Splash oil
Oil capacity [litre]:	1.8
Oil pressure [bar]:	0.6 - 4.0
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m ³ at +20°C] ¹⁾ :	900 (at +20°C / approx. 72 h)
Dimensions W x D x H [mm]:	760 x 1030 x 1630
Weight [kg]:	330
Noise level (measured at 1 m) [dB]:	61

¹⁾ In accordance with EN 12021

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0

Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com

Internet: www.lw-compressors.com